



T3A-IE3 90L2-2 3kW 230/400V 50Hz , . # TS34230023T001-F

DATASHEET

50Hz |

Frame type:	aluminium	Connection:	Δ/Y
Model:	T3A-IE3	Run Capacitor:	
Output:	3 kW	Start Capacitor:	
Rated voltage:	230/400V	Rotor voltage:	
Frame:	90 mm	Rotor connection:	
Poles:	2	Rotor current:	
Frequency:	50 Hz	No load current:	
Rated speed:	2910 RPM	Insulation class:	F
Rated current:	10,8/6,21 A	Temp. rise:	80 K
Locked rotor current(Ia/In):	960%	Service factor:	1
Locked rotor torque(Ma/Mn):	400%	Duty:	S1
Breakdown torque(Ma/Mn):	410%	Amb. temp.:	-20~40 °C
Mounting:	B35	Altitude:	1000 m
Noise level:	74 dB	Protection:	IP55
Approx. weight:	18,5 kg	Cooling:	IC411
Mom. of inertia:	0,003406 kg/m ²	Vibration:	1,6 mm/s
Slip:	3%	Dir. rotation:	BOTH
Rated torque:	9,84 Nm	Starting method:	DIRECT ON LINE
		Coupling:	DIRECT
		Load type:	PARABOLIC CURVE

PERFORMANCE

Output	50%	75%	100%
Efficiency(%):	84,2	87,1	87,1
Power factor:			0,8

STANDARDS

Specification:	IEC60034-1/GB755
Test:	IEC60034-2/GB/T1032
Noise	IEC60034-9/GB10069.3
Vibration:	IEC60034-14/GB10068

BEARING

	NDE	DE
Bearing	6205 2RZ C3	6205 2RZ C3

Regreasing int(h):
Grease amount(g):
Grease polyrexEM:

ACCESSORIES

PTC 150°C

There may be differences between rating plate and calculated values