



OMT1-IE3 315S-4 110kW 400/690V 50Hz , . # AA3E4B1051T0CS

**DATASHEET**

50Hz |

Frame type:	cast iron	Connection:	Δ/Y
Model:	OMT1-IE3	Run Capacitor:	
Output:	110 kW	Start Capacitor:	
Rated voltage:	400/690V	Rotor voltage:	
Frame:	315 mm	Rotor connection:	
Poles:	4	Rotor current:	
Frequency:	50 Hz	No load current:	
Rated speed:	1489 RPM	Insulation class:	F
Rated current:	195/113 A	Temp. rise:	80 K
Locked rotor current(Ia/In):	780%	Service factor:	1
Locked rotor torque(Ma/Mn):	200%	Duty:	S1
Breakdown torque(Ma/Mn):	280%	Amb. temp.:	-20~40 °C
Mounting:	B3	Altitude:	1000 m
Noise level:	76 dB	Protection:	IP55
Approx. weight:	970 kg	Cooling:	IC411
Mom. of inertia:	3,49 kg/m <sup>2</sup>	Vibration:	2,8 mm/s
Slip:	0,7%	Dir. rotation:	BOTH
Rated torque:	705 Nm	Starting method:	DIRECT ON LINE
		Coupling:	DIRECT
		Load type:	PARABOLIC CURVE

**PERFORMANCE**

Output	50%	75%	100%
Efficiency(%):	92,5	95,5	95,4
Power factor:			0,85

**BEARING**

	NDE	DE
Bearing	6319 C3	6319 C3
Regreasing int(h):	4000	4000
Grease amount(g):	45	45
Grease polyrexEM:	Caltex SRI-2	Caltex SRI-2

**STANDARDS**

Specification:	IEC60034-1/GB755
Test:	IEC60034-2/GB/T1032
Noise	IEC60034-9/GB10069.3
Vibration:	IEC60034-14/GB10068

**ACCESSORIES**

PTC 150°C

There may be differences between rating plate and calculated values